



短节距精密滚子链链轮

Short pitch precision roller chain wheels


1"1/4x3/4" 20A-1-2-3 GB1244-1997 DIN8187 ISO/R606		链轮齿部参数MM		
		节距	P	31.75
		滚子直径	d-φ	19.05
		元弧半径	r3	33.5
		倒角宽度	C	4
		齿宽	B1	17.6
		齿宽	b1	17.1
		齿宽	B2	52.9
齿宽	B3	89.10		



A型单排平片链轮
A type simplex plate wheels



A型双排平片链轮
A type duplex plate wheels



A型叁排平片链轮
A type triplex plate wheels

齿数 Z	外径 de	节径 dp	单排链轮 Simplex			双排链轮 Duplex			叁排链轮 Triplex		
			dm	D1	A	dm	D2	A	dm	D3	A
8	98.1	85.96	53	20	40	53	20	75	53	20	110
9	108	92.84	63	20	40	63	20	75	63	20	110
10	117.9	102.74	70	20	40	70	20	75	70	20	115
11	127.8	112.68	77	20	45	80	25	80	80	25	115
12	137.8	122.68	88	20	45	90	25	80	90	25	115
13	147.8	132.65	98	20	45	100	25	80	100	25	115
14	157.8	142.68	108	20	45	110	25	80	110	25	115
15	167.9	152.72	118	20	45	120	25	80	120	25	115
16	177.9	162.75	120	25	50	120	30	80	120	30	115
17	187.9	172.78	120	25	50	120	30	80	120	30	115
18	198	182.85	120	25	50	120	30	80	120	30	115
19	208.1	192.91	120	25	50	120	30	80	120	30	115
20	218.1	202.98	120	25	50	120	30	80	120	30	115
21	228.1	213.04	140	30	55	140	30	80	140	30	115
22	238.3	223.11	140	30	55	140	30	80	140	30	115
23	248.3	233.17	140	30	55	140	30	80	140	30	115
24	258.4	243.23	140	30	55	140	30	80	140	30	115
25	268.4	253.33	140	30	55	140	30	80	140	30	115
26	278.6	263.4	150	30	55	150	30	80	150	30	115
27	288.6	273.49	150	30	55	150	30	80	150	30	115
28	298.7	283.56	150	30	55	150	30	80	150	30	115
29	308.8	293.65	150	30	55	150	30	80	150	30	115
30	318.9	303.75	150	30	55	150	30	80	150	30	115
31	329	313.85	150	30	55	150	30	80	150	30	115
32	339.1	323.91	150	30	55	150	30	80	150	30	115
33	349.2	334.01	150	30	55	150	30	80	150	30	115
34	359.3	344.1	150	30	55	150	30	80	150	30	115
35	369.4	354.2	150	30	55	150	30	80	150	30	115
36	379.5	364.3	150	30	55	150	30	80	150	30	115
37	389.5	374.39	150	30	55	150	30	80	150	30	115
38	399.6	384.49	150	30	55	150	30	80	150	30	115
39	409.7	394.59	150	30	55	150	30	80	150	30	115
40	419.8	404.69	150	30	55	150	30	80	150	30	115

